



DESCRIPTION: -

We have developed epoxy base floor patch repair system with our products you can protect your floors from crumbling and dusting when abrasion, impact, moments or any spillages take place.

FEATURE / ADVANTAGE: -

- Improved flexural and compressive strength than concrete.
- Water proof.
- Crack free.
- Resistant against fuels.
- Shock resistant.
- Better abrasion resistance than concrete.

PHYSICAL PROPERTIES: -

Modulus of elasticity	17000n/ mm2
Adhesion, pull off	2.5-3.5 n/ mm2
Flexural strength	>13 n/ mm2
Compressive strength	>50 n/ mm2
Water absorption %	0%

SUGGESTED USES:-

- Expansion joint of floor,
- For repairing patch of the floor,
- For all types of cracks such as slippage cracking, reflection cracking, edge cracking, blocks cracking etc.,
- Roof top recreation areas.

DIRECTION FOR USE:-

Surface preparation: mechanically clean the surface to remove all loose particle, dirt, oil, grease etc. Vacuum clean to remove all loose material

- Mix VCOBOND EPPL-5900 Part A in to Part B by volume (mixing ratio is 2:1)
- Stir well and add slowly 5 kg FILLER NO 10 into above mixture.
- Again stir well & make it homogenous.
- Fill the patch up to surface level.

PACKING SIZE:-

VCOBOND EPPL-5900 Part A	- 1 lit
VCOBOND EPPL-5900 Part B	- 0.5 lit
VCOBOND FILLER No. 1 0	- 5 kg

STORAGE & SHELF LIFE:-

6 months if sealed packing and if stored in cool dry place in shaded area.

HEALTH & SAFETY:-

While working with VCOBOND materials safety goggles, gloves and safety cloths should be worn at all times. Also observe container labels and instructions in VCOBOND catalog. In case one of component comes in contact with skin wash thoroughly with soap and water adequate ventilation in volume and pattern should be provided in working area. Further precaution emergency showers and eye wash stations.

LEGAL NOTES:-

The information, and, in particular, the recommendations relating to the application and end-use of View Coating products, are given in good faith based on View Coating's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with View Coating's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. View Coating reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.