

VCOBOND AC-5140

Solvent Base

**VCOBOND**

CONSTRUCTION CHEMICALS

DESCRIPTION: -

VCOBOND AC-5140 is a specially formulated solvent base thermoplastic acrylic water repellent coating for just about any surface. VCOBOND AC-5140 provides excellent sealing & water-beading properties, reduces water absorption. It also provides superior breathing properties, crack bridging ability, weathering durability & an excellent resistance to the growth of microorganism. Unlike most other clear coating, this coating may be painted over with latex or oil-based paints.

FEATURE / ADVANTAGE: -

- provides excellent sealing and water-beading properties
- reduces water absorption
- water repellent coating
- UV stable
- Contains No Silicones...No Waxes...Interior or Exterior Use... Environmentally Safe!

PHYSICAL PROPERTIES: -

Finish	Glossy & smooth Matt available on request
Color	Transparent
Solids	38 ± 2
Specific gravity	1.02 +/- .005
Drying Time	Touch dry - 30 min Ready for recoat - 3 hrs.

SUGGESTED USES:-

Concrete, plaster, masonry, gypsum, timber and metals. Interiors & Exteriors.

DIRECTION FOR USE:-

- The surface should be clean, dry and free from all dirt, grease, oils, waxes, mildew, curing agents, and other surface contaminants that may cause coating failure.
- Remove all loose and peeling paint and lightly sand glossy surfaces.
- **VCOBOND AC-5140** is supplied ready to use. Can be thinned using VCOBOND EPSOLVE as per requirement. Mix thoroughly prior to use. Easily applied with a quality brush, roller, airless spray and low-pressure hand pump sprayer.
- Always apply material to test panel prior to general application.

PACKING SIZE: -

0.5lit, 1lit, 5lit, 10lit & 20lit.

COVERAGE: -

Covers approximately 4-5 square meter per liter depending up on type of application & porosity of the surface to be treated.

STORAGE & SHELF LIFE: -

6 months if sealed packing and if stored in cool dry place in shaded area.

HEALTH & SAFETY: -

Prevent contact of solution with the eyes and mouth. Gloves and rubber gloves must be worn when handling. Liquid splashed on the skin must be rinsed off quickly. If the solution is splashed into the eyes, wash it away with liberal quantity of water and obtain immediate medical attention. Use of mask & safety goggles is must. Clean up any spills, painting tools and equipment with solvent.

LEGAL NOTES: -

The information, and, in particular, the recommendations relating to the application and end-use of View Coating products, are given in good faith based on View Coating's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with View Coating's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. View Coating reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.