

**VCOBOND AC-5140**

Water Base

**VCOBOND**

CONSTRUCTION CHEMICALS

**DESCRIPTION:-**

VCOBOND AC-5140 Water-Based acrylic & styrene co-polymer is a clear finish that creates a hard, durable coating and can be used interior wood & stone. Dries quickly and cleans up easily with soap and water. Great for use on interior surfaces such as floors, cabinets, doors, furniture.

**FEATURE / ADVANTAGE:-**

- provides excellent sealing and water-beading properties
- reduces water absorption
- water repellent coating
- UV stable
- Hard, Tough, Clear, Flexible & Glossy Film,
- Excellent Wet scrub & Abrasion.

**PHYSICAL PROPERTIES:-**

Finish	Glossy & smooth
Color	Bluish translucent emulation
Solids	49 ± 2
Specific gravity	1.02 +/- .005
Viscosity	30-80 poise
Drying Time	Touch Dry- 30 min Ready to recoat – 3 hours

**SUGGESTED USES:-**

Roof Tiles, Brick, Cement, and Concrete Block – Masonry, Plaster, and Simulated brick, stone & wood.

**DIRECTION FOR USE:-**

- The surface should be clean, dry and free from all dirt, grease, oils, waxes, mildew, curing agents, and other surface contaminants that may cause coating failure.
- Remove all loose and peeling paint and lightly sand glossy surfaces.
- **VCOBOND AC-5140** is supplied ready to use. Can be thinned using water as per requirement. Mix thoroughly prior to use. Easily applied with a quality brush, or roller.
- Always apply material to test panel prior to general application. .

**PACKING SIZE:-**

0.5lit, 1lit, 5lit, 10lit & 20lit.

**COVERAGE:-**

Covers approximately 4-5 square meter per liter depending up on type of application & porosity of the surface to be treated.

**STORAGE & SHELF LIFE:-**

6 months if sealed packing and if stored in cool dry place in shaded area.

**HEALTH & SAFETY:-**

Prevent contact of solution with the eyes and mouth. Gloves and rubber gloves must be worn when handling. Liquid splashed on the skin must be rinsed off quickly. If the solution is splashed into the eyes, wash it away with liberal quantity of water and obtain immediate medical attention. Use of mask & safety goggles is must. Clean up any spills, painting tools and equipment with solvent.

**LEGAL NOTES:-**

The information, and, in particular, the recommendations relating to the application and end-use of View Coating products, are given in good faith based on View Coating's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with View Coating's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. View Coating reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.